

DSA ELECTRODES

IrO₂-Ta₂O₅ Coated Titanium Electrode Tube

Iridium tantalum oxide coated are considered optimum choice as anodes in various industries for its strong corrosion resistance in acid environment, low overpotential for oxygen evolution, great physical stability and its environmental safety. Compared with traditional electrodes, Ir-Ta MMO electrodes presence better electrochemical stability under sulfate/chloride environment and longer service life.

+1 (713) 799 3884

+1 (281) 501 8398

www.jenningsanodes.com

sales@jenningsanodes.com



Jennings Anodes USA Inc.

Address: 3115 N Fry Rd Ste 303, Katy, TX 77449



Accumulated decades of coated titanium electrode technology, JAU kept providing our clients with high quality Ir-Ta MMO electrode regarding multiple oxygen-evolution systems. JAU electrodes have been applied to industries like copper foil production, electroplating, cathodic protection, organic synthesis, acid solution electrolysis, electrowinning, etc.

Applications

1. Copper Foil Production
2. Cathodic Protection
3. Waste Water Treatment
4. Copper Electrowinning
5. Organic Synthesis
6. Metal Surface Treatment
7. Electrodialysis

Features

1. Highly stable even under acid environment
2. Great current efficiency
3. Low overpotential for oxygen evolution
4. Long service life expectancy
5. Reusable substrate



Specifications

Electrode Substrate	Titanium ASTM B338-2017 Gr1/2
Coating Composition	IrO ₂ , Ta ₂ O ₅
Working Temperature	<60 C
Working PH Environment	1-12
Current Capacity	<12000 A/m ²
Dimensions	Customized